

Technical datasheet: VERO-S NSE-T3 138 (Standard)

Functional description:

The clamping operation is performed based on an integrated spring assembly. The resulting clamping of the pin is self-locking. The pull-down force can be increased by up to 300% by actuating of the standardized integrated turbo function, which occurs due to an additional short pressurization of the piston surface. By pressurization (> 5 bar) of the module the clamping slides open and the clamping pin can be removed.

Characteristics	Description
Opening pressure	Min. 5 bar / Max. 7 bar
Weight	4.4 kg
Repeatability: with SPA 40 with SPG 40	< 0.005 mm < 0.002 mm
Clamping slide monitoring	Monitoring of the clamping slide position via pressure sensing
Flexible actuation	The actuation of the module can be realized via air connections either on the side or from the bottom.
Turbo function	Increasing of the pull-down force by an additional pressure impulse in the spring chamber
Hermetically sealed	Maintenance-free, IP 67 (DIN EN 60529)
Corrosion-resistant	All functional parts are made of hardened, stainless steel
Self-locking system	Clamping pin remains in the module in case of a pressure drop
Short taper centering	Precise centering by quick and easy joining via entry radii
Application of proven and fundamental safety principles in terms of DIN 13849-2: technical attachment A	Is applied for example by using of reliable springs, using of proper materials and manufacturing processes, proper dimensioning, etc.
Patented dual stroke system	Therefore highest pull-down forces
Definition of the clamping module in terms of MRL Directive 2006/42/EC	Incomplete machine
PL (Performance Level)	Not applicable because the module is no safety component
Elimination of errors	Release of the clamped quick-change pallet system without adjacent unlocking signal

Technical datasheet: VERO-S NSE-T3 138 (Standard)

Page 2 / 2

Pull-down force in axial direction

without turbo function = **7 000 N**
 with turbo function = **24 000 N** (6 bar)



Lateral force with turbo-function

$$F_{lateral} = F_{pull-down\ force} * \mu$$

$$= 24\ 000\ N * 0.1$$

$$F_{lateral} = \mathbf{2\ 400\ N}$$


[Lateral force without relative movement]



Tilting moment clamping-station with turbo-function

1-way

$$M_{tilt\ Module} = \mathbf{280\ Nm}$$
 (determined empirically)



Tilting moment clamping station with turbo-function


4-way

Pitch 200 mm x 200 mm

$$M_{tilt} = \mathbf{5\ 000\ Nm} \quad F_{lateral} = \mathbf{9\ 600\ N}$$

Pitch 300 mm x 300 mm

$$M_{tilt} = \mathbf{7\ 000\ Nm} \quad F_{lateral} = \mathbf{9\ 600\ N}$$



 **More details in quotation**